



# TRANSflo

## Automatic Transmission Fluid



### Features & Benefits

- Excellent corrosion and foam prevention
- Safe for all seals
- Promotes transmission cleanliness

### Specifications

✓ Meets Requirements

Specification	TRANSflo
Allison C-3, C-4	✓
Allison TES-389	✓
American Motors ATF +3 (MS 7176-E)	✓
Audi 5HP LT71141	✓
Audi G 052 162-A1/A2 (ZF Lifeguard 5)	✓
BMW 7045E, ETL-8072B, LA2634	✓
CAT TO-2	✓
Chrysler ATF+2, +3	✓
Ford MERCON®	✓
Ford WSS M2C 138CJ, 166H	✓
GM DEXRON® II, IID, IIE, IIIG, IIIH	✓
GM TASA	✓
Hyundai/Kia DEX-II/SP-II	✓
Jaguar JLM 20292, 20238	✓
Mazda ATF M-III, & F-I	✓
MB ZF 4HP20	✓
NAG 1 (Chrysler, Jeep, Cherokee)	✓
Opel/GM 19 40 700, 19 40 767, 21005966 Transaxle, 22 17466	✓
Peugot/Citreon Z 000169756, AL4 Automatic gearbox oil (#9730.AE)	✓
Porsche 000 043 205 09, 999 917 547 00, Z 000169756	✓
Renault Matic D2, DPO/AL4	✓
Volvo CE 97340	✓
Volvo 97325 & 97335	✓
Vickers M2950-S, I-286-S	✓
VW G US 000 162	✓
ZF TE-ML 05L, 09, 21L	✓

### Typical Results

Test Method	TRANSflo
COLOUR	RED
VISCOSITY (D445) cSt @ 40°C	33.2
cSt @ 100°C	7.1
VISCOSITY INDEX (D2270)	186
POUR POINT (D97) (°C)	-42
FLASH POINT (D93) (°C)	190
DENSITY @ 15°C (D4052) (kg/L)	0.85

**TRANSflo** is a premium product specially formulated for automatic transmissions manufactured in 2005 and earlier for General Motors, Ford, and Chrysler vehicles.

**TRANSflo** provides excellent low-temperature fluidity and maintains its film-thickness at temperatures over 149°C for bearing and gear lubrication.

**TRANSflo** meets specifications by Allison as a type C-4 fluid and can be used in Ford model C-6 automatic transmissions built on or after 1977.

**TRANSflo** can also be used in certain power steering, hydro-static systems and power-shift transmissions where this type of oil is recommended.

**TRANSflo** may also be used as hydraulic fluid due to its excellent low-temperature fluidity and red colour.

### Sizes & Order Codes

Size	TRANSflo
946mL / 1 US Qt	F0020815
3.78L / 1 US gal	F0020826
18.9L / 5 US gal Pail	F0082240
205L / 54.2 US gal Drum	F0015650
1000L / 264 US gal Tote	F0020860
1000L / 264 US gal Bulk Tote	F0105901
Bulk	B0020801

[www.irvingoil.com/lubricants](http://www.irvingoil.com/lubricants)  
1.800.574.5823

Always consult your owner's manual for verification of fluid type and grade!

Supporting data available to demonstrate acceptable performance. Check with your sales associate for latest product approvals.

Please note, these are typical performance indicators and can change without notice.

This data sheet replaces previous versions prior to Feb 13<sup>th</sup>, 2023.

[www.irvingoil.com/lubricants](http://www.irvingoil.com/lubricants) 1.800.574.5823