

IRVING MARINE DEF

Marine Grade Diesel Exhaust Fluid



Features & Benefits

- Meets ISO 18611-1:2014
- Non-toxic, non-polluting, non-hazardous and non-flammable
- Reduces harmful emissions
- Increases fuel efficiency



Typical Results

Characteristics	Units	Typical	Min	Max
Urea Content	% (m/m)	40.1	39.0	41.0
Density at 20°C	kg/L	1.1142	1.050	1.177
Refractive Index at 20°C	-	1.3958	1.3934 ¹	1.3982
Alkalinity (as Ammonia)	% (m/m)	<0.1	-	0.5
Biuret	% (m/m)	0.3	-	0.8
Aldehydes	mg/kg	1.3	-	100
Insoluble matter	mg/kg	2.6	-	50
Phosphates	mg/kg	0.3	-	1
Calcium	mg/kg	<0.1	-	1
Iron	mg/kg	<0.1	-	1
Copper	mg/kg	<0.1	-	1
Zinc	mg/kg	<0.1	-	1
Chromium	mg/kg	<0.1	-	1
Nickel	mg/kg	<0.1	-	1
Aluminum	mg/kg	<0.1	-	1
Magnesium	mg/kg	<0.1	-	1
Sodium	mg/kg	<0.1	-	1
Potassium	mg/kg	<0.1	-	1
Identity (FTIR)	-	Pass	-	-

¹ Minimum Refractive Index based on 0.0% Biuret

² Maximum Refractive Index based on 0.8% Biuret


IRVING MARINE DEF (Diesel Exhaust Fluid) is a 40% Aqueous Urea Solution (AUS 40) manufactured with high-purity urea mixed with quality electro-deionized (EDI) water designed to meet the specifications of ISO 18611-1:2014 for NO_x emissions of large diesel engines on ships.

IRVING MARINE DEF is produced to exceed the quality characteristics defined in ISO 18611-1. Typical results of the contaminants analysed in the result chart are far lower than the maximum set out by the ISO 18611-1 standard. Typical results are within the stringent quality specification of ISO 22241-1:2019 for DEF contaminants.

IRVING MARINE DEF is certified as a Marine Diesel Exhaust Fluid AUS 40 by the American Petroleum Institute (API).

Sizes & Order Codes

Size	Code
208 L / 55 US Gal Plastic Drum	F0129950
1250 L / 3183 US Gal Tote	F0129960
Bulk	B0103101



www.irvingoil.com/lubricants
1.800.574.5823

Always consult your owner's manual for verification of fluid type and grade!
Supporting data available to demonstrate acceptable performance. Check with your sales associate for latest product approvals.

Please note, these are typical performance indicators and can change without notice.

This data sheet replaces previous versions prior to June 9, 2023.

www.irvingoil.com/lubricants 1.800.574.5823

IRVING MARINE DEF

Marine Grade Diesel Exhaust Fluid



ISO 18611-3:2014 - Shelf Life as a Function of Storage Temperature

Constant Ambient Storage Temperature (°C)	Minimum Shelf Life (Months)
0 – 25	18
<30	12
<35	6
>35	Possible significant loss of shelf life: check every batch before use

NOTE: The main factors taken into account to define the shelf life in this table are the ambient storage temperature and the initial alkalinity of AUS 40. The difference in evaporation between vented and non-vented storage containers is another factor.

Never store Marine DEF in direct sunlight!

Table Reference:

International Organization for Standardization. (2014). Ships and marine technology – Marine NOx reduction agent AUS 40 – Part 3: Handling, transportation, and storage (ISO Standard No. 18611-3:2014). Retrieved from <https://www.iso.org/obp/ui/#iso:std:iso:18611:-3:ed-1:v1:en>



www.irvingoil.com/lubricants
1.800.574.5823